

HIGH TECH INNOVATIONS FOR THE
GLASS INDUSTRY „MADE IN BAVARIA“.



AP TWIN

POWDER SPRAYER FOR FLOAT-/FLAT GLASS

AP TWIN is an enhancement of the proven and tested Grafotec nozzle system. With an application width from 3,300 mm and a double batcher the AP TWIN powder sprayer permits a clever adaption to production widths and gaps as well as the application of two different separating agents during the production process due to two separate 15 liters powder reservoirs.

- Optimized for the special demands of float glass and flat glass production.
- Nozzle system with „fixed spray angle“.
- Can be easily integrated into the production lines already in use.
- Robust design for low-maintenance continuous use.
- Adaptable to changes in product conditions.
- Uses powdered separator agents with minimum loss.



HIGH TECH INNOVATIONS FOR THE
GLASS INDUSTRY „MADE IN BAVARIA“.



AP TWIN

POWDER SPRAYER FOR FLOAT-/FLAT GLASS

AP TWIN is an enhancement of the proven and tested Grafotec nozzle system.

With an application width from 3,300 mm and a double batcher the AP TWIN powder sprayer permits a clever adaption to production widths and gaps as well as the application of two different separating agents during the production process due to two separate 15 liters powder reservoirs.

Technical Specifications:

Application Type:	Nozzle system with „fixed spray angle“
Separator Agent:	All separator agents for float/flat glass currently on the market.
Application Width:	> 3300 mm
Number of Nozzles:	2x12/6 2x16/4x2 2x12/12
Powder Reservoir:	2 x 15 Litres
Special Features:	<ul style="list-style-type: none">✓ Automatic and manual application width adjustment.✓ Automatic speed adjustment.✓ Maintenance free and frequency-controlled side channel blower.

All AP TWIN systems can be individually adjusted according to your needs and product lines.



Nozzle system:

Special plastic nozzles with „self cleaning effect“ provide optimal distribution of the powdered release agents.



Dosing system with injection module:

Two special dosage rollers guarantee accurate dosing and repeat accuracy in the application of the separator agent. The injection module is resistant of deposits and blockages.



Distribution Module:

The distribution module for uniform distribution of the separating agent from the nozzle with automatic application width adjustment.



Grafotec Spray Systems GmbH

Keimstraße 7a
D-86420 Diedorf

Fon +49 821 88588 170
Fax +49 821 88588 188

E-Mail: info@grafotec.com
Internet: www.grafotec.com